


SEAL SPEC R105-A

seal-mart | 



description

rotary shaft seal made of elastomer which has an outer casing reinforced with impregnated fabric. the fabric reinforcement is bonded firmly to the elastomer component. the sealing ring is energised by a spring. on request with additional dust lips

- + particularly robust static part
- + lasting radial contact pressure
- + highly wear-resistant
- + with design measures, e.g., metal support for the sealing lip, higher pressures are possible
- + overpressure requires the usage of endless seals
- + back-up ring drawings and installation instructions for open seals are available.

category of profile

molded/standard/trade product or machined with minor design change.

single acting rotary seal


the R105-A seal is designed for use as a rotary seal

area of application

sealing of rotating machine elements such as shafts, hubs and axle in large machinery and plant construction, e.g. wind energy generators, construction machinery, rolling mills and shipbuilding. R105-A can be used in difficult installation conditions.

function

the R104-A type has a groove running vertically to the axle. the R105-A type have a circular groove on the outside diameter in addition to the vertically running groove as the R104-A. the R104-A & R105-A type are applied back to back in pairs wherever relubrication from the outside is necessary, e.g. when separating of media or protecting against the invasion of dust, dirt and water spray.



SEAL SPEC R105-A

operating parameter & material

sealing element	material	spring	temperature	max surface speed	max pressure
NBR 80 with impregnated cotton fabric		rust & acid resistant steel 1.4301 (AISI 304)	-30 °C ... +100 °C	20 m/s	0,5 bar

the stated operation conditions represent general indications. it is recommended not to use all maximum values simultaneously. surface speed limits apply only to the presence of adequate lubrication film.

surface quality

surface roughness	Rtmax (µm)	Ra (µm)
contact area	≤2,5	≤0,6
housing	≤15	≤4

tolerance recommendation

seal housing tolerance	
Ød	h9
ØD	H8

fitting & installation

suitable tool should be used for installation. R105-A are slightly squashed into the axially accessible housing bore. R105-A have surplus height and are additionally axially pressed into the installation housing. increased radial pressure is guaranteed by the radial and axial deformation. R104-A & R105-A rotary shaft seals are both installed back to back. special values apply with regard to the requirements for shafts, housing bores and eccentricities. these details can be coordinator with our technical departement.

seal & housing recommendations

please note that we are able to produce those profiles to your specific need or any non standard housing. for detail measurements, please see seal-mart catalog...

